

THE CORE 200(T)

TECHNICAL DATA SHEET


Technical data

Model	CORE 200	CORE 200T
Stock code	8500	8505
Tank capacity	7-8 litres	7-8 litres
Dimensions*	200x600x850/900	200x600x850/900
Basket*	158x285x135	158x285x135
Output per hour (frozen product)	19-23 kg/h	23-27 kg/h
Voltage	3N400V	3N400V
Heating power	7.2 kW	9 kW
Amperage	10A per phase	13A per phase
Heating element	1	1
Temperature range	95°C – 190° C	95°C – 190° C
Protection index	IPX4	IPX4
Net weight	41 kg	41 kg
Power cable	2.5m	2.5m
Frying surface	W169xD338mm	W169xD338mm

* Width x Depth x Height (mm)



Supplied with lid, basket, oil bucket, crumb filter, element lifting hook and mains cable



THE CORE 200(T)

TECHNICAL DATA SHEET

Features and benefits

- Electromechanical thermostat with overheat protection
- Ergonomic thermostat knob for easy temperature control
- Integrated Sicotronic interface
- Intelligent adjustment for optimised performance and precise temperature control ($\pm 6^{\circ}\text{C}$)
- Maximum insulation to optimise efficiency and heat retention, minimising energy loss
- Cool zone for waste collection below the heating element, slowing down oil degradation
- Fryer can be heated for cleaning with water (95°C)
- Rounded corners and a pivoting heating element, with an intermediate stop position, for easy cleaning
- Folding lid for easy storage (inside fryer door)
- MELT Position: melts solid fat without burning it
- Easy to locate element RESET button
- High quality components and finish to meet the highest standards
- Stainless steel, strong and durable
- Adjustable height legs with fixed castors on rear
- Turbo option, ideal for frying frozen food
- Swiss Made: manufactured at the Valentine Fabrique factory in Romanel-sur-Morges
- IPX4 rating / 3-year warranty / 20-year tank warranty
- 20-year availability of spare parts

Options

- Built-in installation
- Turbo
- Other voltages available on request

Accessories

- Microfilter with support frame
- Fishplate
- Batter bowl
- Splashguard
- Interlock channel
- VITO oil filtration
- VITO oil tester

Certifications

- CB, UL, CE, UKCA

Technical drawings (mm)

